



**PLUS SERIES™**

## **PLUS SERIES™**

### **The Power of Maroon™ for Premium Performance, Durability and Easier Maintenance**

With over 80 years of experience, Trojan Battery—the most trusted name in deep cycle technology—offers its most popular batteries with new innovative features.

**Trojan's Plus Series batteries are designed to deliver unrivaled premium benefits:**

- Trojan's SureVent™ flip-top vent cap system makes watering your battery safer, faster, and easier—minimizing your time spent on maintenance
- Trojan's vent well features a built-in maximum level indicator for precise watering each and every time—resulting in better performance and longer life
- Trojan's embedded terminals withstand the heat and stress of the most demanding applications—resulting in higher durability

Trojan's proprietary Maxguard® Advanced Design Separator and exclusive Alpha Plus® paste formulation are still included. Together, these patented technologies help extend the life of your battery, sustain performance and lower overall maintenance costs.

**We offer outstanding technical support provided by full-time applications engineers. Call 800-423-6569 or 562-236-3000 for more information or visit us at [www.trojanbattery.com](http://www.trojanbattery.com).**

*Plus Series is available worldwide through Trojan's Master Distributor Network.*

*Clean energy for life™*

# PLUS SERIES™

## Product Specifications

BCI GROUP SIZE	TYPE	CAPACITY <sup>A</sup> Minutes			CAPACITY <sup>B</sup> Amp-Hours (AH)		TERMINAL TYPE (See Below)	HANDLE or BRACKET	DIMENSIONS <sup>C</sup> Inches (mm)			WEIGHT lbs. (kg)
		@25 Amps	@56 Amps	@75 Amps	5 Hr Rate	20 Hr Rate			L	W	H <sup>D</sup>	
<b>6 VOLT DEEP CYCLE BATTERIES</b>												
GC2	T-105 Plus	447	-	115	185	225	1,2,3	Bracket	10 3/8 (264)	7 1/8 (181)	10 11/16 (272)	62 (28)
GC2	T-125 Plus	488	-	132	195	240	1,2,3	Bracket	10 3/8 (264)	7 1/8 (181)	10 11/16 (272)	66 (30)
GC2H	T-145 Plus	530	-	145	215	260	1,2,3	Bracket	10 3/8 (264)	7 1/8 (181)	11 1/2 (292)	72 (33)
<b>12 VOLT DEEP CYCLE BATTERIES</b>												
N/A	T-1275 Plus	280	102	-	120	150	1,2,3	Bracket	12 7/8 (327)	7 1/8 (181)	10 11/16 (272)	82 (37)
N/A	J150 Plus	280	-	70	120	150	1,2,3	Rope	13 13/16 (351)	7 1/8 (181)	11 1/8 (283)	84 (38)

- A. The number of minutes a battery can deliver when discharged at a constant rate at 80°F (27°C) and maintain a voltage above 1.75 V/cell. Capacities are based on peak performance.
- B. The amount of amp-hours (AH) a battery can deliver when discharged at a constant rate at 80°F (27°C) for the 20 Hr and 86°F (30°C) for the 5 Hr rate and maintain a voltage above 1.75 V/cell. Capacities are based on peak performance.
- C. Dimensions are based on maximum size. Dimensions may vary depending on type of handle or terminal.
- D. Dimensions taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.

### \*SureVent™ flip-top caps



**Easier Maintenance**

### Built-in maximum water level indicator



**Precise Watering:  
Better Performance**

### Embedded Terminals



**Increased Durability**

\*Patent Pending

## TERMINAL CONFIGURATIONS



EHPT



ELPT



AP



For a Trojan Master Distributor near you, call 800-423-6569 or 562-236-3000 or visit [www.trojanbattery.com](http://www.trojanbattery.com).